

Sylproof Tubular LED - DALI

Sylproof Tubular LED 1X600 DALI NW
0047598



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED




PRODUCT OVERVIEW

| | |
|-----------------------------|------------------------------------|
| Product name | Sylproof Tubular LED 1X600 DALI NW |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Acrylic PMMA |
| Mount | Ceiling surface mounting |
| Environment | Interior |
| General application | Logistics & Industry |
| ETIM Class | EC000109 |
| Fixture luminous flux (lm) | 1338 |
| Luminous flux (lm) | 1338 |
| Luminaire efficacy (lm/W) | 102.92 |
| LOR (%) | 100 |
| Colour temperature (K) | 4000 |
| Light colour | Neutral White |
| CRI (Ra) | 80 |
| Colour Consistency (SDCM) | 3 |
| Photobiological Risk Group | RG0 |
| Total power consumption (W) | 13 |
| Electrical protection | Class I |
| Control gear type | Electronic ballast |
| Dimmable | Yes |
| Minimum dimming level (%) | 90 |
| Housing colour | Transparent |
| IP rating | IP66 |
| IK rating | IK06 |
| Product EAN number | 5410288475981 |

PHOTOMETRY

Sylproof Tubular LED - DALI Sylproof Tubular LED 1X600 DALI NW 0047598



| | | | |
|-----|---------------|--------------------------|-------------------|
| 0.5 | 1.14 1.78 | E(0°) E(C90) E(C0) | 1670 240 86 |
| 1.0 | 2.28 3.56 | E(0°) E(C90) E(C0) | 433 60 22 |
| 1.5 | 3.41 5.35 | E(0°) E(C90) E(C0) | 188 27 11 |
| 2.0 | 4.55 7.13 | E(0°) E(C90) E(C0) | 104 15 6 |
| 2.5 | 5.69 8.91 | E(0°) E(C90) E(C0) | 67 10 4 |
| 3.0 | 6.83 10.69 | E(0°) E(C90) E(C0) | 46 7 3 |

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 181.4°)
— C90 - C270 (Half beam angle: 97.4°)

TECHNICAL DRAWINGS

