


Blacklight BL368 Linear T5

F8W T5 BL368
0000089



Product features

- Blacklight BL368 T5 UV-A lamp with spectral peak at 368nm



PRODUCT OVERVIEW

| | |
|----------------------------|----------------------|
| Product name | F8W T5 BL368 |
| Technology | Special applications |
| Lamp shape | Tubular shape |
| Type | T5 |
| Cap/Base | G5 |
| Lamp finish | Frosted/Coated |
| Fixture rating | Enclosed |
| General application | SPG |
| ETIM Class | EC002962 |
| E-number FI | 4940422 |
| Light colour | BL368 Blacklight |
| Wattage (W) | 8.00 |
| Product Voltage (V) | 56 |
| Dimmable | No |
| Average life (Nominal) (h) | 10000 |
| Product EAN number | 5410288000893 |

DATA TABLE

General data

| | |
|----------------------------------|----------------------|
| Product name | F8W T5 BL368 |
| Technology | Special applications |
| Lamp shape | Tubular shape |
| Type | T5 |
| Cap/Base | G5 |
| Lamp finish | Frosted/Coated |
| Fixture rating | Enclosed |
| General application | SPG |
| Operating temperature range (°C) | -15°C - 50°C |
| ETIM Class | EC002962 |
| E-number FI | 4940422 |

Blacklight BL368 Linear T5

F8W T5 BL368

0000089

Optical data

| | |
|--|------------------|
| Ambient temperature for maximum luminous flux (°C) | 25 |
| Light colour | BL368 Blacklight |
| Adjustable chromaticity | N |

Electrical data

| | |
|-----------------------|-----------|
| Wattage (W) | 8.00 |
| Current (A) | 0.145 |
| Mains voltage (V) | 230-240V~ |
| Product Voltage (V) | 56 |
| Control gear required | Yes |
| Transformer required | No |
| Dimmable | No |
| Drive current (mA) | 145 |

Lifetime data

| | |
|----------------------------|-------|
| Average life (Nominal) (h) | 10000 |
|----------------------------|-------|

Physical data

| | |
|-------------------------------------|-------------|
| Nominal Product Length (mm) | 300.0 |
| Nominal Product Diameter (mm) | 16 |
| Max. Length base to base (mm) - A | 288.3 |
| Length base to pin Min-Max (mm) - B | 293.0-295.4 |
| Max. Lamp Length (mm) - C/L | 302.5 |
| Max. Lamp Diameter (mm) - D | 17.0 |
| Weight (kg) | 0.023 |

Packaging

| | |
|---------------------------------------|----------------|
| Single packaging type | Carton |
| Product EAN number | 5410288000893 |
| Packaging single length / height (cm) | 30.3 |
| Packaging single width (cm) | 1.9 |
| Packaging single depth (cm) | 1.9 |
| DUN14 (outer) | 15410288000890 |
| Units per outer package | 25 |
| Packaging outer length / height (cm) | 32.0 |
| Packaging outer width (cm) | 11.0 |
| Packaging outer depth (cm) | 10.5 |

Safety data


| | |
|--|--------------------------------|
| Lamp mercury content (mg) | 2.30 |
| Optimal operating condition (°C) | -15-50 |
| Breakage cleaning instructions | Applicable |
| Recommendation for disposal at end of life | Applicable |
| Special purpose lamp | Yes |
| Intended purpose | Flykilling - Insect attraction |
| Suitable for household illumination | No |

Blacklight BL368 Linear T5 F8W T5 BL368 0000089

Safety message

Not suitable for household

PHOTOMETRY



TECHNICAL DRAWINGS

