

Start Waterproof T8

START WATERPROOF T8 PC 2x58 EB
0045821



Product features

- Start Waterproof T8 weatherproof luminaire, Polycarbonate housing, Polycarbonate Diffuser, 2 x 58W, Non Dimmable Electronic Ballast, IP66, IK08, Lamp not included, To be used with LFL tubes



PRODUCT OVERVIEW

Product name	START WATERPROOF T8 PC 2x58 EB
Technology	Fluorescent
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC002892
Warranty	2 years
Light colour	N/A
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral
Housing colour	Grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288458212

DATA TABLE

General data

Product name	START WATERPROOF T8 PC 2x58 EB
Technology	Fluorescent
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
Operating temperature range (°C)	-20°C - 25°C
ETIM Class	EC002892
Warranty	2 years

Optical data

Light colour	N/A
Adjustable chromaticity	N

Electrical data

Mains voltage (V)	220-240V~
-------------------	-----------

Start Waterproof T8 START WATERPROOF T8 PC 2x58 EB 0045821

Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral
Transformer required	Yes
Nominal Frequency (Hz)	50/60Hz

Physical data

Housing colour	Grey
IP rating	IP66
IK rating	IK08
Diffuser finish	Prismatic
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1577
Nominal Product Width (mm)	116
Nominal Product Height (mm)	100
Weight (kg)	2.215


Packaging

Single packaging type	Carton
Product EAN number	5410288458212
Packaging single length / height (cm)	157.7
Packaging single width (cm)	11.6
Packaging single depth (cm)	9.4
DUN14 (outer)	05410288458212
Units per outer package	1
Packaging outer length / height (cm)	157.7
Packaging outer width (cm)	11.6
Packaging outer depth (cm)	9.4

Safety data

Optimal operating condition (°C)	-20-25
----------------------------------	--------

PHOTOMETRY



Start Waterproof T8 START WATERPROOF T8 PC 2x58 EB 0045821

TECHNICAL DRAWINGS

