

## START eco Flood Flat

*START eco Flood Flat IP65 4500lm 840*  
0047969



### Product features


- The new Start eco Flood Flat comes with improved design. The streamlined, durable, lightweight die-cast aluminium body makes it a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black die-cast aluminum housing, white reflector, 4750 lm, 50 W, 95 lm/W, 4000K, drive current 193 mA, non dimmable, CRI>80, IP65, IK07, Class I, lumen maintenance L70:B50: 30000 hrs, 193 x 190 x 48 mm (L x W x H). Weight: 0.785kg. Energy class: A++ A+ A.



### PRODUCT OVERVIEW

Product name	START eco Flood Flat IP65 4500lm 840
Technology	LED
Housing	Aluminium
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4579437
Warranty	3 years
Fixture luminous flux (lm)	4750
Luminaire efficacy (lm/W)	95
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Beam Angle (°)	110
Photobiological Risk Group	RG1
Total power consumption (W)	50
Electrical protection	Class I
Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK07
Product EAN number	5410288479699

### PHOTOMETRY



## START eco Flood Flat

*START eco Flood Flat IP65 4500lm 840*  
0047969

---

### TECHNICAL DRAWINGS

---

