

## DeltaWing LED - DALI dimmable & Microwave sensor

*DELTAWING LED69 DALI MW 3K 1200*  
0044898



### Product features

- Low profile surface and suspended LED diffuser luminaire, 1218mm x 200mm, 3000K Warm White, DALI dimmable, Microwave sensor, 6984lm, 71W, lifespan: 55,000 hours L90B10, A++ A+ A




### PRODUCT OVERVIEW

Product name	DELTAWING LED69 DALI MW 3K 1200
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Environment	Internal
General application	Education, Hospitality, Logistics & Industry, Office, Retail
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	6984
Luminaire efficacy (lm/W)	98.36
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Beam Angle (°)	102
Glare control	< 24
Total power consumption (W)	71
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	95
Housing colour	White
IP rating	IP44
IK rating	IK08
Product EAN number	5410288448985

### PHOTOMETRY

## DeltaWing LED - DALI dimmable & Microwave sensor DELTAWING LED69 DALI MW 3K 1200 0044898



Distance (m)	Cone diameter (m)	Beam diameter (m)	Beam diameter (ft)	Illuminance (lx)
0.5	1.24 1.64	0.50	1.64	790 92 92
1.0	2.48 3.28	1.00	3.28	197 24 12
1.5	3.72 4.91	1.50	4.91	83 115 83
2.0	4.96 6.59	2.00	6.59	49 25 38
2.5	6.20 8.19	2.50	8.19	32 20 23
3.0	7.44 9.83	3.00	9.83	22 18 16

Distance (m)      Cone diameter (m)      Illuminance (lx)

— C0 - C180 (Half beam angle: 111.2°)  
 — C90 - C270 (Half beam angle: 102.2°)

### TECHNICAL DRAWINGS

