

Sylproof Tubular LED - DALI

Sylproof Tubular LED 1X1500 DALI NW
0047600



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED




PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 1X1500 DALI NW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	3352
Luminous flux (lm)	3352
Luminaire efficacy (lm/W)	106.07
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	32
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	90
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476001

PHOTOMETRY

Sylproof Tubular LED - DALI Sylproof Tubular LED 1X1500 DALI NW 0047600



0.5	1.17 1.92	E(0°) E(90°) E(180°)	4133 993 238
1.0	2.35 3.61	E(0°) E(90°) E(180°)	1033 141 58
1.5	3.52 5.41	E(0°) E(90°) E(180°)	499 53 25
2.0	4.70 7.22	E(0°) E(90°) E(180°)	248 35 15
2.5	5.87 9.02	E(0°) E(90°) E(180°)	166 23 9
3.0	7.05 10.62	E(0°) E(90°) E(180°)	115 16 7

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 182.0°)
— C90 - C270 (Half beam angle: 99.2°)

TECHNICAL DRAWINGS

