

## ToLEDo Superia T5 ECG

TOLEDO SUPERIA T5 HO 4FT 4100LM 865  
0029509



### Product features

- 60,000 hours average rated lifetime (L70 F50). Last 3 times longer than 54W 1149mm fluorescent tri-phosphor T5 lamp. High switching cycles - 200,000X. High lumen efficacy -152lm/W. Omni-directional light distribution and wide beam angle. Minimum and maximum operating temperature: -20°C to 50°C. Glass construction and polycarbonate end-caps. Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast. Works only with compatible electronic ballasts. Ideal for factories, parking lots, supermarkets, department stores, schools and offices.



### PRODUCT OVERVIEW

Product name	TOLEDO SUPERIA T5 HO 4FT 4100LM 865
Technology	LED
Watt (Rated) (W)	27
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4740606
E-number SE	8293579
Warranty	5 years
Luminous flux (lm)	4100
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Beam Angle (°)	220
Wattage (W)	27
Product Voltage (V)	50
Dimmable	No
Average life (Nominal) (h)	60000
Product EAN number	5410288295091

### DATA TABLE

#### General data

Product name	TOLEDO SUPERIA T5 HO 4FT 4100LM 865
Technology	LED
Watt (Rated) (W)	27
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740606
E-number SE	8293579
Warranty	5 years

## ToLEDo Superia T5 ECG

TOLEDO SUPERIA T5 HO 4FT 4100LM 865

0029509

### Optical data

Luminous flux (lm)	4100
Luminous flux (Rated) (lm)	4100
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Beam Angle (°)	220
Lumen maintenance at end of nominal life (%)	70

### Electrical data

Wattage (W)	27
Watt (Rated) - High frequency (W)	27
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	<2
Current (A)	0.6
Product Voltage (V)	50
Lamp power factor	0.92
No. Of switching cycles before premature failures	>200000
Dimmable	No
kWh per 1000 hours burning time	30

### Lifetime data

Average life (Nominal) (h)	60000
Average life (Rated) (h)	60000

### Physical data

Nominal Product Diameter (mm)	1149
Weight (kg)	0.148

### Packaging

Single packaging type	Carton
Product EAN number	5410288295091
Packaging single length / height (cm)	116.5
Packaging single width (cm)	1.8
Packaging single depth (cm)	1.8
DUN14 (outer)	15410288295098
Units per outer package	10
Packaging outer length / height (cm)	122.0
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	8.0

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture



ToLEDo Superia T5 ECG  
*TOLEDO SUPERIA T5 HO 4FT 4100LM 865*  
0029509

---