

Emergency kit PANEL 80V EMERGENCY KIT 0047579



#### Product features

6-80V emergency accessory pack for panels, includes 3 x 4Ah D Cell Ni-Cd, 5W power consumption, LED current limit 350mA, Battery current limit 1100mA, 24 hour charge period, Power factor 0.9, mains frequency 50Hz, charge current 200mA nominal. Do not use with surface mounting kits with panels.



### PRODUCT OVERVIEW

Product name	PANEL 80V EMERGENCY KIT
Technology	Accessory
Housing	Steel
Environment	Interior
General application	Education, Hospitality, Office, Retail
ETIM Class	EC000471
E-number SE	7016423
Warranty	3 years
Electrical protection	Class I
Control gear type	Electronic ballast
Product EAN number	5410288475790

#### DATA TABLE

General data	
Product name	PANEL 80V EMERGENCY KIT
Technology	Accessory
Housing	Steel
Environment	Interior
General application	Education, Hospitality, Office, Retail
ETIM Class	EC000471
E-number SE	7016423
Warranty	3 years
Optical data	
Optical data Adjustable chromaticity	Ν
•	N 3
Adjustable chromaticity	
Adjustable chromaticity Emergency duration (h)	
Adjustable chromaticity Emergency duration (h) Electrical data	3
Adjustable chromaticity Emergency duration (h) Electrical data Mains voltage (V)	3 230-240V~



# Emergency kit PANEL 80V EMERGENCY KIT 0047579

Physical data	
Nominal Product Length (mm)	300
Nominal Product Width (mm)	90
Nominal Product Height (mm)	42
Weight (kg)	1.3
Recessed Depth (mm)	29
Packaging	
Single packaging type	Carton
Product EAN number	5410288475790
Packaging single length / height (cm)	38.0
Packaging single width (cm)	10.0
Packaging single depth (cm)	6.0
DUN14 (outer)	05410288475790
Units per outer package	1
Packaging outer length / height (cm)	63.505
Packaging outer width (cm)	34.0
Packaging outer depth (cm)	35.0

## **TECHNICAL DRAWINGS**

