Beacon LED Projector - Framing
Beacon Muse Framing Projector O/B 4000K Three Circuit Track - Silver 2055189



Product features

Beacon Projector offers precision light exactly where it is needed. The Framing Projector has four adjustable arms allowing the beam to be framed to the desired size shape (square/rectangle or irregular 4 sided shapes). High colour rendering CRI 97 typical. IR/UV free light source without heat radiation. LED technology provides an energy efficient solution with reduced maintenance costs.

















PRODUCT OVERVIEW

Product name	Beacon Muse Framing Projector O/B 4000K Three Circuit Track - Silver
Technology	LED
Housing	Aluminium
Mount	Track mounting
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	-
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	95
Colour Consistency (SDCM)	3
Beam Angle (°)	10
Photobiological Risk Group	RG1
Total power consumption (W)	26
Product Voltage (V)	240
Electrical protection	Class II
Control gear mounting	Integral
Housing colour	Silver
IP rating	IP20
IK rating	IK02
Product EAN number	5025768551897

DATA TABLE

General data	
Product name	Beacon Muse Framing Projector O/B 4000K Three Circuit Track - Silver
Technology	LED



Beacon LED Projector - Framing
Beacon Muse Framing Projector O/B 4000K Three Circuit Track - Silver 2055189

Housing	Aluminium
Mount	Track mounting
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Warranty	5 years
Optical data	
Fixture luminous flux (lm)	-
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	95
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	10
Distribution type	Adjustable
Photobiological Risk Group	RG1
Electrical data	
Total power consumption (W)	26
Mains voltage (V)	230V~
Product Voltage (V)	240
Electrical protection	Class II
Control gear mounting	Integral
Transformer required	Yes
Nominal Frequency (Hz)	50/60Hz
Nonlinal Frequency (HZ)	30/00HZ
Lifetime data	
Lifespan L70 B50	50000
Dhysical data	
Physical data	
Housing colour	Silver
IP rating	IP20
IK rating	IK02
Nominal Product Width (mm)	185
Nominal Product Height (mm)	215
Nominal Product Diameter (mm)	80
Weight (kg)	1.365
Packaging	
Single packaging type	Carton
Product EAN number	5025768551897
Packaging single length / height (cm)	32.0
Packaging single width (cm)	15.5
Packaging single depth (cm)	13.0
DUN14 (outer)	05025768551897
Units per outer package	1



Beacon LED Projector - Framing
Beacon Muse Framing Projector O/B 4000K Three Circuit Track - Silver 2055189

Packaging outer length / height (cm)	32.0	
Packaging outer width (cm)	15.5	
Packaging outer depth (cm)	13.0	

TECHNICAL DRAWINGS

