

START DOWNLIGHT IP44 205 START Downlight 205 IP44 1-10V 1975Lm 840 0030345

Product features

Ceiling recessed LED downlight IP44 (from the front), with only 60mm product depth and 205mm cutout. Supplied with TCI 1-10V Jolly driver (125421). Ideal replacement for 1x42W CFL downlights. The polycarbonate diffuser allows for a wider light distribution and increased spacings between luminiares. Die-cast aluminium body, 1975LM, 20W, 99lm/W, 4000K, Driver Current: 600mA, CRI80, 74° beam angle, IP44 from the front, IK07, (HxW) 60x205mm, Class 2, 220-240V




PRODUCT OVERVIEW


Product name	START Downlight 205 IP44 1-10V 1975Lm 840
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Logistics & Industry, Office
ETIM Class	EC001744
E-number FI	4278181
Warranty	5 years
Fixture luminous flux (Im)	1750
Luminous flux (Im)	1975
Luminaire efficacy (Im/W)	88
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	80
Glare control	< 26
Photobiological Risk Group	RG0
Total power consumption (W)	20
Electrical protection	Class II
Control gear type	Other
Dimmable	Yes
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288303451

PHOTOMETRY



START DOWNLIGHT IP44 205 START Downlight 205 IP44 1-10V 1975Lm 840 0030345





TECHNICAL DRAWINGS

