

## Emergency kit PANEL 50-240V EMERGENCY KIT 0047595



### Product features

- 50-240V emergency accessory pack for LED light sources, includes 3 x 4Ah D Cell Ni-Cd, 2.4W power consumption, LED current limit 240mA, Battery current limit 960mA, 24 hour charge period, mains frequency 50Hz, trickle charge current 80-130mA nominal. Do not use with surface mounting kits with panels.



### PRODUCT OVERVIEW

Product name	PANEL 50-240V EMERGENCY KIT
Technology	Accessory
Housing	Steel
Mount	Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Office, Retail
ETIM Class	EC000471
E-number SE	7016422
Warranty	2 years
Electrical protection	Class I
Product EAN number	5410288475950

### DATA TABLE

#### General data

Product name	PANEL 50-240V EMERGENCY KIT
Technology	Accessory
Housing	Steel
Mount	Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Office, Retail
ETIM Class	EC000471
E-number SE	7016422
Warranty	2 years

#### Optical data

Emergency duration (h)	3
------------------------	---

#### Electrical data

Current (A)	0.02
Mains voltage (V)	230-240V~
Lamp power factor	0.9
Electrical protection	Class I

## Emergency kit

*PANEL 50-240V EMERGENCY KIT*  
0047595

### Physical data

Nominal Product Length (mm)	400
Nominal Product Width (mm)	90
Nominal Product Height (mm)	40
Weight (kg)	1.55

### Packaging

Single packaging type	Carton
Product EAN number	5410288475950
Packaging single length / height (cm)	46.0
Packaging single width (cm)	12.5
Packaging single depth (cm)	5.0
DUN14 (outer)	15410288475957
Units per outer package	1
Packaging outer length / height (cm)	47.0
Packaging outer width (cm)	33.0
Packaging outer depth (cm)	36.0