

HSI-TD

Hsi-Td150w/Wdl Uvs Rx7s Slv

0020232



Product features



PRODUCT OVERVIEW

Product name	Hsi-Td150w/Wdl Uvs Rx7s Slv
Technology	HID
Watt (Rated) (W)	150
Type	HSI-TD
Cap/Base	RX7s-24
Lamp finish	Clear
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail
ETIM Class	EC000037
Luminous flux (lm)	12500
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Wattage (W)	150
Product Voltage (V)	95
Average life (Nominal) (h)	12000
Product EAN number	5410288202327

DATA TABLE

General data

Product name	Hsi-Td150w/Wdl Uvs Rx7s Slv
Technology	HID
Watt (Rated) (W)	150
Type	HSI-TD
Cap/Base	RX7s-24
Lamp finish	Clear
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail
ETIM Class	EC000037

Optical data

Luminous flux (lm)	12500
--------------------	-------

HSI-TD

Hsi-Td150w/Wdl Uvs Rx7s Slv

0020232

Luminous flux (Rated) (lm)	12500
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	3000
Light colour	Warm White
Colour Code	830
CRI (Ra)	80
Adjustable chromaticity	N
Rated lumen maint. factor (%) at 4000 h 50Hz	82
Rated lumen maint. factor (%) at 6000 h 50Hz	80
Rated lumen maint. factor (%) at 8000 h 50Hz	79
Rated lumen maint. factor (%) at 12000 h 50Hz	76

Electrical data

Wattage (W)	150
Current (A)	1.8
Product Voltage (V)	95
Control gear required	Yes
Transformer required	No
kWh per 1000 hours burning time	165

Lifetime data

Average life (Nominal) (h)	12000
Average life (Rated) (h)	12000
Life T90	8000
Rated survival factor (%) at 2000 h 50Hz	100
Rated survival factor (%) at 4000 h 50Hz	100
Rated survival factor (%) at 6000 h 50Hz	97
Rated survival factor (%) at 8000 h 50Hz	90
Rated survival factor (%) at 12000 h 50Hz	50
Rated survival factor (%) at 16000 h 50Hz	70

Physical data

Max. Lamp Diameter (mm) - D	25
Weight (kg)	0.029

Packaging

Single packaging type	Carton
Product EAN number	5410288202327
Packaging single length / height (cm)	20.0
Packaging single width (cm)	3.5
Packaging single depth (cm)	3.5
DUN14 (inner)	15410288202324
Units per inner package	10
Packaging inner length / height (cm)	20.5

HSI-TD

Hsi-Td150w/Wdl Uvs Rx7s Slv


0020232

Packaging inner width (cm)	18.6
Packaging inner depth (cm)	7.9
DUN14 (outer)	35410288202328
Units per outer package	120
Packaging outer length / height (cm)	49.8
Packaging outer width (cm)	39.5
Packaging outer depth (cm)	23.4

Safety data

Lamp mercury content (mg)	10.50
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Suitable for household illumination	No

TECHNICAL DRAWINGS



HSI-TD	70W	150W	250W
L	117.6	135.4	161.6
D	22	25	27.5