

Sylproof Tubular - Accessories

Tubular 5P SPLITTER CONNECTOR (X1)

0042492



Product features

- TUBULAR 5P SPLITTER CONNECTOR (X1)



PRODUCT OVERVIEW

| | |
|----------------------------|------------------------------------|
| Product name | Tubular 5P SPLITTER CONNECTOR (X1) |
| Technology | Accessory |
| Housing | Aluminium |
| Mount | Track mounting |
| General application | Logistics & Industry |
| ETIM Class | EC002557 |
| Warranty | 2 years |
| LOR (%) | 100 |
| CRI (Ra) | 93 |
| Colour Consistency (SDCM) | 3 |
| Beam Angle (°) | 34 |
| Photobiological Risk Group | RG1 |
| Electrical protection | Class II |
| Control gear type | Electronic ballast |
| Housing colour | White |
| IP rating | IP20 |
| IK rating | IK02 |
| Product EAN number | 5410288424927 |

DATA TABLE

General data

| | |
|---------------------|------------------------------------|
| Product name | Tubular 5P SPLITTER CONNECTOR (X1) |
| Technology | Accessory |
| Housing | Aluminium |
| Mount | Track mounting |
| General application | Logistics & Industry |
| ETIM Class | EC002557 |
| Warranty | 2 years |

Optical data

| | |
|---------------------------|-----|
| LOR (%) | 100 |
| CRI (Ra) | 93 |
| Colour Consistency (SDCM) | 3 |
| Adjustable chromaticity | N |

Sylproof Tubular - Accessories

Tubular 5P SPLITTER CONNECTOR (X1)

0042492

| | |
|----------------------------|-----|
| Beam Angle (°) | 34 |
| Photobiological Risk Group | RG1 |

Electrical data

| | |
|-----------------------|--------------------|
| Electrical protection | Class II |
| Control gear type | Electronic ballast |
| Transformer required | Yes |
| Glow Wire Test (°C) | 650 |

Lifetime data

| | |
|------------------|-------|
| Lifespan L70 B50 | 72000 |
| Lifespan L70 B10 | 72000 |
| Lifespan L80 B50 | 72000 |
| Lifespan L80 B20 | 72000 |
| Lifespan L80 B10 | 72000 |
| Lifespan L90 B50 | 43000 |
| Lifespan L90 B20 | 36000 |
| Lifespan L90 B10 | 33000 |

Physical data

| | |
|-----------------------------|-------|
| Housing colour | White |
| IP rating | IP20 |
| IK rating | IK02 |
| Nominal Product Width (mm) | 200 |
| Nominal Product Height (mm) | 250 |
| Weight (kg) | 0.1 |

Packaging

| | |
|---------------------------------------|----------------|
| Single packaging type | Plastic |
| Product EAN number | 5410288424927 |
| Packaging single length / height (cm) | 4.0 |
| Packaging single width (cm) | 8.4 |
| Packaging single depth (cm) | 38.0 |
| DUN14 (outer) | 15410288424924 |
| Units per outer package | 10 |
| Packaging outer length / height (cm) | 42.5 |
| Packaging outer width (cm) | 8.5 |
| Packaging outer depth (cm) | 39.0 |

TECHNICAL DRAWINGS

