# Concord

### Beacon LED Projector - Framing Beacon Muse Framing Projector O/B 3000K Three Circuit Track - White 2055177



#### Product features

 Beacon Projector offers precision light exactly where it is needed. The Framing Projector has four adjustable arms allowing the beam to be framed to the desired size shape (square/rectangle or irregular 4 sided shapes). High colour rendering CRI 97 typical. IR/UV free light source without heat radiation. LED technology provides an energy efficient solution with reduced maintenance costs.



#### PRODUCT OVERVIEW

| Product name                | Beacon Muse Framing Projector O/B 3000K Three Circuit Track - White |
|-----------------------------|---|
| Technology                  | LED   |
| Housing                     | Aluminium   |
| Mount                       | Track mounting  |
| Environment                 | Interior  |
| General application         | Hospitality, Museums & Galleries, Retail                            |
| ETIM Class                  | EC001744  |
| Warranty                    | 5 years   |
| Fixture luminous flux (Im)  | -   |
| Colour temperature (K)      | 3000  |
| Light colour                | Warm White  |
| CRI (Ra)                    | 95  |
| Colour Consistency (SDCM)   | 3   |
| Beam Angle (°)              | 10  |
| Photobiological Risk Group  | RG1   |
| Total power consumption (W) | 26  |
| Product Voltage (V)         | 240   |
| Electrical protection       | Class II  |
| Control gear mounting       | Integral  |
| Housing colour              | White   |
| IP rating                   | IP20  |
| IK rating                   | IK02  |
| Product EAN number          | 5025768551774   |
| Light source included       | INTEGRATED LED  |

### DATA TABLE

| General data |   |
|--------------|---|
| Product name | Beacon Muse Framing Projector O/B 3000K Three Circuit Track - White |
| Technology   | LED   |

## Concord

## Beacon LED Projector - Framing Beacon Muse Framing Projector O/B 3000K Three Circuit Track - White 2055177

| Housing                               | Aluminium                                |
|---------------------------------------|--|
| Mount                                 | Track mounting                           |
| Environment                           | Interior                                 |
| General application                   | Hospitality, Museums & Galleries, Retail |
| ETIM Class                            | EC001744                                 |
| Warranty                              | 5 years                                  |
| Ontional data                         |  |
| Optical data                          |  |
| Fixture luminous flux (Im)            | -  |
| Colour temperature (K)                | 3000                                     |
| Light colour                          | Warm White                               |
| CRI (Ra)                              | 95                                       |
| Colour Consistency (SDCM)             | 3  |
| Adjustable chromaticity               | Ν  |
| Beam Angle (°)                        | 10                                       |
| Distribution type                     | Adjustable                               |
| Photobiological Risk Group            | RG1                                      |
| Electrical data                       |  |
| Total power consumption (W)           | 26                                       |
| Mains voltage (V)                     | 230V~                                    |
| Product Voltage (V)                   | 240                                      |
| Electrical protection                 | Class II                                 |
| Control gear mounting                 | Integral                                 |
| Transformer required                  | Yes                                      |
| Nominal Frequency (Hz)                | 50/60Hz                                  |
| ······                                |  |
| Lifetime data                         |  |
| Lifespan L70 B50                      | 50000                                    |
| Physical data                         |  |
| Housing colour                        | White                                    |
| IP rating                             | IP20                                     |
| IK rating                             | IK02                                     |
| Nominal Product Width (mm)            | 185                                      |
| Nominal Product Height (mm)           | 215                                      |
| Nominal Product Diameter (mm)         | 80                                       |
| Weight (kg)                           | 1.365                                    |
| 0 (0)                                 |  |
| Packaging                             |  |
| Single packaging type                 | Carton                                   |
| Product EAN number                    | 5025768551774                            |
| Packaging single length / height (cm) | 32.0                                     |
| Packaging single width (cm)           | 15.5                                     |
| Packaging single depth (cm)           | 13.0                                     |
| DUN14 (outer)                         | 05025768551774                           |
| Units per outer package               | 1  |
| Packaging outer length / height (cm)  | 32.0                                     |
| Packaging outer width (cm)            | 15.5                                     |
|                                       |  |



## Beacon LED Projector - Framing Beacon Muse Framing Projector O/B 3000K Three Circuit Track - White

2055177

Packaging outer depth (cm) 13.0

#### **TECHNICAL DRAWINGS**

