Beacon LED Projector - Gobo

Beacon Muse Gobo Projector O/B 3000K Single Circuit Track - Black 2055167



Product features

 Beacon Projector offers precision light exactly where it is needed. The Gobo Projector with the use of ROSCO filters allow you to project a still image printed/cut/lasered onto a specially made glass/metal/acetate filter - for example a company logo, text, shapes, images. High colour rendering CRI 97 typical. IR/UV free light source without heat radiation. LED technology provides an energy efficient solution with reduced maintenance costs.















PRODUCT OVERVIEW

Product name	Beacon Muse Gobo Projector O/B 3000K Single Circuit Track - Black
Technology	LED
Housing	Aluminium
Mount	Track mounting
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	95
Colour Consistency (SDCM)	3
Beam Angle (°)	10
Photobiological Risk Group	RG1
Total power consumption (W)	26
Product Voltage (V)	240
Electrical protection	Class I
Control gear mounting	Integral
Housing colour	Black
IP rating	IP20
IK rating	IK02
Product EAN number	5025768551675
Light source included	INTEGRATED LED

DATA TABLE

General data	
Product name	Beacon Muse Gobo Projector O/B 3000K Single Circuit Track - Black
Technology	LED
Housing	Aluminium
Mount	Track mounting



Beacon LED Projector - Gobo Beacon Muse Gobo Projector O/B 3000K Single Circuit Track - Black 2055167

Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
O :: 1.1.	
Optical data	
Fixture luminous flux (lm)	-
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	95
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	10
Distribution type	Adjustable
Photobiological Risk Group	RG1
Electrical data	
Total power consumption (W)	26
Mains voltage (V)	230V~
Product Voltage (V)	240
Electrical protection	Class I
Control gear mounting	Integral
Transformer required	Yes
Transformer required Nominal Frequency (Hz)	Yes 50/60Hz
Nominal Frequency (Hz) Lifetime data	50/60Hz
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data	50/60Hz 50000
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour	50/60Hz
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating	50/60Hz 50000 Black
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating	50/60Hz 50000 Black IP20
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm)	50/60Hz 50000 Black IP20 IK02
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm)	50/60Hz 50000 Black IP20 IK02 185
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Diameter (mm)	50/60Hz 50000 Black IP20 IK02 185 215
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm)	50/60Hz 50000 Black IP20 IK02 185 215 80
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Diameter (mm)	50/60Hz 50000 Black IP20 IK02 185 215 80
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg)	50/60Hz 50000 Black IP20 IK02 185 215 80
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging	50/60Hz 50000 Black IP20 IK02 185 215 80 1.365
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm)	50/60Hz 50000 Black IP20 IK02 185 215 80 1.365 Carton
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm)	50/60Hz 50000 Black IP20 IK02 185 215 80 1.365 Carton 5025768551675
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm)	50/60Hz 50000 Black IP20 IK02 185 215 80 1.365 Carton 5025768551675 32.0
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm)	50/60Hz 50000 Black IP20 IK02 185 215 80 1.365 Carton 5025768551675 32.0 15.5
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm)	50/60Hz 50000 Black IP20 IK02 185 215 80 1.365 Carton 5025768551675 32.0 15.5 13.0
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer)	50/60Hz 50000 Black IP20 IK02 185 215 80 1.365 Carton 5025768551675 32.0 15.5 13.0 05025768551675
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package	50/60Hz 50000 Black IP20 IK02 185 215 80 1.365 Carton 5025768551675 32.0 15.5 13.0 05025768551675 1



Beacon LED Projector - Gobo Beacon Muse Gobo Projector O/B 3000K Single Circuit Track - Black 2055167

TECHNICAL DRAWINGS

