

T8 Luxline Plus F70W/T8/840 (184) 0001094




Product features



PRODUCT OVERVIEW

Product nameF70W/T8/840 (184)FechnologyFluorescentWatt (Rated) (W)69.50amp shapeTube, double-endedTypeT8 Luxline PlusCap/BaseG13amp finishFrosted/CoatedFixture ratingOpenGeneral applicationEducation, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & ConsumerETIM ClassEC000108
Watt (Rated) (W)69.50Lamp shapeTube, double-endedTypeT8 Luxline PlusCap/BaseG13Lamp finishFrosted/CoatedFixture ratingOpenGeneral applicationEducation, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & ConsumerETIM ClassEC000108
Lamp shapeTube, double-endedTypeT8 Luxline PlusCap/BaseG13Lamp finishFrosted/CoatedFixture ratingOpenGeneral applicationEducation, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & ConsumerETIM ClassEC000108
TypeT8 Luxline PlusCap/BaseG13amp finishFrosted/CoatedFixture ratingOpenGeneral applicationEducation, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & ConsumerETIM ClassEC000108
Cap/Base G13 Lamp finish Frosted/Coated Fixture rating Open General application Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer ETIM Class EC000108
Lamp finish Frosted/Coated Fixture rating Open General application Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer ETIM Class EC000108
Fixture ratingOpenGeneral applicationEducation, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & ConsumerETIM ClassEC000108
General applicationEducation, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & ConsumerETIM ClassEC000108
Galleries, Office, Retail, Residential & Consumer ETIM Class
E-number FI 4940246
E-number Norway 3800917
Luminous flux (Im) 6200
Colour temperature (K) 4000
Light colour Cool White
CRI (Ra) 85
Colour Variation Initial (SDCM) SDCM5
Photobiological Risk Group Not applicable
Nattage (W) 70.00
Product Voltage (V) 128
Dimmable Yes
Average life (Nominal) (h) 20000
Product EAN number 5410288010946

PHOTOMETRY



TECHNICAL DRAWINGS



T8 Luxline Plus *F70W/T8/840 (184)* 0001094

