


Beacon XL Muse Xicato®

BEACON XL MUSE Xicato® 4K O/B DIM LS3 Black
2059899



Product features

- Integrated LED spotlight with Xicato® Artist LED Module, black RAL 9005, unique soft-touch ring, adjustable beam angle from a 10° spot to a 72° flood, compact and minimalist design, ideal for museum, gallery and high-end retail applications, die-cast aluminium body, passive cooling heatsink, beam angle: 10° spot to 72° flood, optics: aspheric glass lens, colour temperature: 4000K neutral white, total system power: 35W, total fixture output: 681/1697lm, luminaire efficacy: 48lm/W, LOR: 100%, super high colour rendering: Ra 98 typical, R9 value at 90, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 1050mA, electronic driver, dimmable via on-board potentiometer, power factor: 0.95, electrical protection: CLASS I, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal use.




PRODUCT OVERVIEW

Product name	BEACON XL MUSE Xicato® 4K O/B DIM LS3 Black
Technology	LED
Housing	Aluminium
Mount	Track mounting
General application	Museums & Galleries
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	681/1697
Luminaire efficacy (lm/W)	48
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	98
Colour Variation Initial (SDCM)	SDCM2
Photobiological Risk Group	RG1
Total power consumption (W)	35
Electrical protection	Class II
Control gear type	Other
Control gear mounting	Integral
Dimmable	Yes
Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Product EAN number	5025768598991

PHOTOMETRY

Beacon XL Muse Xicato®

BEACON XL MUSE Xicato® 4K O/B DIM LS3 Black
2059899



TECHNICAL DRAWINGS

