Lumiance

Instar Eco Kit LED Adjustable - Dimmable INST ECO KIT LED ADJ WH 3000K DIMMABLE 3079451



Product features

25° tiltable, IP23 (from the front) Accent downlight perfect for 50W Halogen retrofits. Optimal solution
in size and luminous efficiency for hospitality and accent and display lighting applications with a 36°
beam and 462 lumen output. The downlight provides 3000K CCT and also comes including a
dimmable driver.



PRODUCT OVERVIEW

DATA TABLE

General data	
Product name	INST ECO KIT LED ADJ WH 3000K DIMMABLE
Technology	LED

Lumiance

Instar Eco Kit LED Adjustable - Dimmable INST ECO KIT LED ADJ WH 3000K DIMMABLE 3079451


Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Hospitality
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4271078
E-number SE	7465558
Warranty	3 years
Optical data	
Fixture luminous flux (Im)	462
Luminaire efficacy (Im/W)	46.2
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	83
Colour Consistency (SDCM)	5
Adjustable chromaticity	5 N
Beam Angle (°)	36
Distribution type	Direct
Distribution type	Direct
Electrical data	
Total power consumption (W)	10
Mains voltage (V)	220-240V~
Electrical protection	Class II
Control gear type	Electronic ballast
Transformer required	Yes
Minimum dimming level (%)	70
Drive current (mA)	800
Physical data	
Housing colour	White
IP rating	IP23/20
-	IF23/20 IK02
IK rating Diffuser finish	
	Transparent Other
Diffuser material	Other 78
Nominal Product Length (mm)	
Nominal Product Width (mm)	78
Nominal Product Height (mm)	62 78
Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or	78 68
Diameter in mm)	00
Weight (kg)	0.408
Recessed Depth (mm)	110
Packaging	
Single packaging type	Carton
Product EAN number	8711971794516
	07110717010

Lumiance

Instar Eco Kit LED Adjustable - Dimmable INST ECO KIT LED ADJ WH 3000K DIMMABLE 3079451

Packaging single length / height (cm)	15.1
Packaging single width (cm)	11.4
Packaging single depth (cm)	9.1
DUN14 (outer)	18711971794513
Units per outer package	20
Packaging outer length / height (cm)	31.9
Packaging outer width (cm)	24.4
Packaging outer depth (cm)	47.9

PHOTOMETRY



TECHNICAL DRAWINGS

