


START eco Panel Flat UGR19 625x625

START eco Panel Flat UGR19 625x625 3000lm 840
0047367



Product features

- Competitive, edge lit LED flat low glare panel (UGR<19). Low Flicker, 30 W, Neutral White, 4000 K, 3000 lumens, 100 lm/W, 30000 hours lifetime (L70), PMMA opal diffuser, aluminium frame, steel body, electronic non dimmable driver. (HxWxD) 8.5 x 621 x 621 mm



PRODUCT OVERVIEW

Product name	START eco Panel Flat UGR19 625x625 3000lm 840
Technology	LED
Environment	Interior
General application	Education, Office
ETIM Class	EC002892
Warranty	3 years
Fixture luminous flux (lm)	3000
Luminaire efficacy (lm/W)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	80
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	30
Electrical protection	Class II
LED Flickering Rate	Ultra low (5% or less)
IP rating	IP40/20
IK rating	IK03
Product EAN number	5410288473673

DATA TABLE

General data

Product name	START eco Panel Flat UGR19 625x625 3000lm 840
Technology	LED
Environment	Interior
General application	Education, Office
Operating temperature range (°C)	-10°C - 40°C
Performance ambient temperature Tq (°C)	25

START eco Panel Flat UGR19 625x625

START eco Panel Flat UGR19 625x625 3000lm 840
0047367

ETIM Class	EC002892
Warranty	3 years

Optical data

Fixture luminous flux (lm)	3000
Luminaire efficacy (lm/W)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	80
Glare control	< 19
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	30
Mains voltage (V)	220-240V~
Electrical protection	Class II
Drive current (mA)	900
Inrush Current (A)	14
Inrush Duration (µs)	300
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)

Lifetime data

Lifespan L70 B50	30000
------------------	-------

Physical data

IP rating	IP40/20
IK rating	IK03
Nominal Product Length (mm)	621
Nominal Product Width (mm)	621
Nominal Product Height (mm)	8.5
Weight (kg)	2.7

Packaging

Single packaging type	Carton
Product EAN number	5410288473673
Packaging single length / height (cm)	70.5
Packaging single width (cm)	65.0
Packaging single depth (cm)	3.8
DUN14 (outer)	15410288473670
Units per outer package	52
Packaging outer length / height (cm)	147.5
Packaging outer width (cm)	68.5
Packaging outer depth (cm)	108.0

Safety data

Optimal operating condition (°C)	-10-40
----------------------------------	--------

START eco Panel Flat UGR19 625x625


START eco Panel Flat UGR19 625x625 3000lm 840
0047367

PHOTOMETRY

0.5	0.95 0.96	E(0°) E(C90) E(C0)	9696 1082 1069
1.0	1.99 1.92	E(0°) E(C90) E(C0)	1424 273 267
1.5	2.84 2.69	E(0°) E(C90) E(C0)	633 121 119
2.0	3.78 3.65	E(0°) E(C90) E(C0)	356 86 87
2.5	4.73 4.61	E(0°) E(C90) E(C0)	228 44 43
3.0	5.67 5.77	E(0°) E(C90) E(C0)	158 30 30

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 87.8°)
— C90 - C270 (Half beam angle: 96.8°)



TECHNICAL DRAWINGS

