

Sylproof Tubular LED - Electronic

Sylproof Tubular LED 2X1200 EB NW
0047584



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED



PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 2X1200 EB NW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	4264
Luminous flux (lm)	4264
Luminaire efficacy (lm/W)	109.33
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	39
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288475844


PHOTOMETRY

Sylproof Tubular LED - Electronic Sylproof Tubular LED 2X1200 EB NW 0047584

Distance [m]	Cone diameter [m]	E0°	E10°	E30°	E45°	E60°	E75°	E90°
0.5	1.19 2.23	4834	1445	484	271	161	107	71
1.0	2.38 4.45	1209	361	121	68	42	28	19
1.5	3.58 6.68	637	191	60	35	21	14	9
2.0	4.77 8.90	392	116	36	20	12	8	5
2.5	5.96 11.13	195	58	18	10	6	4	3
3.0	7.15 13.35	134	40	13	7	4	3	2

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 135.0°)
— C90 - C270 (Half beam angle: 100.0°)



TECHNICAL DRAWINGS

