

Sylproof Superia LED G3 fixed output SYLPROOF SUPERIA LED G3 1200mm Twin 4K QC 0048739

Product features



Sylproof Superia, integrated LED weatherproof luminaire with quick connector, UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface and wall mounting. L 1278 mm x W 110 mm x H 78 mm size, Polycarbonate housing, Polycarbonate diffuser, Non dimmable, 4000K, CRI80, 5400 lm, 36 W, 150 lm/W, nominal average life (h):50000, energy class: A++ A+ A
























PRODUCT OVERVIEW


Product name	SYLPROOF SUPERIA LED G3 1200mm Twin 4K QC
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (Im)	5400
Luminaire efficacy (lm/W)	150
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	100
Photobiological Risk Group	RG1
Total power consumption (W)	36
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288487397

PHOTOMETRY



Sylproof Superia LED G3 fixed output SYLPROOF SUPERIA LED G3 1200mm Twin 4K QC 0048739





TECHNICAL DRAWINGS

