

## Sylproof Tubular LED - Microwave sensor

*Sylproof Tubular LED 1X1500 EB MW NW*  
0047612



### Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED




### PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 1X1500 EB MW NW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	3352
Luminous flux (lm)	3352
Luminaire efficacy (lm/W)	106.07
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	31.6
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476124

### PHOTOMETRY

## Sylproof Tubular LED - Microwave sensor

*Sylproof Tubular LED 1X1500 EB MW NW*  
0047612



0.5	1.17 1.92	E(0°) E(C90) E(C0)	4133 593 238
1.0	2.35 3.61	E(0°) E(C90) E(C0)	1033 144 58
1.5	3.52 5.41	E(0°) E(C90) E(C0)	689 95 38
2.0	4.70 7.22	E(0°) E(C90) E(C0)	517 71 28
2.5	5.87 9.02	E(0°) E(C90) E(C0)	414 56 22
3.0	7.05 10.62	E(0°) E(C90) E(C0)	331 45 17

Distance [m]      Cone diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 110.0°)  
— C90 - C270 (Half beam angle: 99.2°)

## TECHNICAL DRAWINGS

