

DeltaWing LED - Electronic DELTAWING LED72 EB 4K 1200 0044875

Product features



Low profile surface and suspended LED diffuser luminaire, 1218mm x 200mm, 4000K Neutral White, Electronic, 7260lm, 71W, lifespan: 55,000 hours L90B10, A++ A+ A

















PRODUCT OVERVIEW


Product name	DELTAWING LED72 EB 4K 1200
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Environment	Internal
General application	Education, Hospitality, Logistics & Industry, Office, Retail
ETIM Class	EC002892
E-number FI	4274308
E-number SE	7014023
Warranty	5 years
Fixture luminous flux (lm)	7260
Luminaire efficacy (lm/W)	102.25
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Beam Angle (°)	102
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	71
Product Voltage (V)	240
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	White
IP rating	IP44
IK rating	IK08
Product EAN number	5410288448756



DeltaWing LED - Electronic DELTAWING LED72 EB 4K 1200 0044875

PHOTOMETRY





TECHNICAL DRAWINGS

