

Syl-Line electrical unit SYL-LINE GT3R 4K DALI DASY WH EM 0042136

Product features

Syl-Line LED Gear Tray, 4000K Neutral White, DALI Dimming, Double Asymmetric Beam, White, 3 hour Maintained Emergency




PRODUCT OVERVIEW

Product name	SYL-LINE GT3R 4K DALI DASY WH EM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting, Suspended
Environment	Interior
General application	Logistics & Industry, Retail
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (Im)	6535
Luminous flux (Im)	6535
Luminaire efficacy (Im/W)	120
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Photobiological Risk Group	RG0
Total power consumption (W)	54
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	99
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5410288421360

PHOTOMETRY

SYLVANIA

Syl-Line electrical unit SYL-LINE GT3R 4K DALI DASY WH EM 0042136



TECHNICAL DRAWINGS

4	+ 200		E.	430		100.00					101
									1780	08	+0
	-		-	-		-	10		1340	340	*6
	+	_			_	_					
- 10	*				-	_					
					1						
		÷		œ	+	,					
				5	- 08			-			
				ŕ	-		.00	1			
				ľ			.00	1			
				ŕ	100		.00	1			