

## Beacon LED


BEACON 93CRI 3K NARROW BEAM L1 TRAILING EDGE WHITE

2059581



### Product features

- Integrated LED spotlight, white RAL 9016, compact and minimalist design, ideal for retail, display, museum and gallery applications, die-cast aluminium body, passive cooling heatsink, beam angle: 12° narrow beam, optics: Fresnel lens for controlled beam, colour temperature: 3000K warm white, total system power: 21W, total fixture output: 1512lm, luminaire efficacy: 72lm/W, LOR: 100%, colour rendering: Ra 93 typical, LED Chromacity: 3 step MacAdam ellipse, lifetime: >72,000 hours at L80B50, energy class: A++, A+, A, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, trailing edge dimmable, power factor: 0.9 electrical protection: CLASS II, 1-circuit track adaptor, suitable for Concord Lytespan 1 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø80x130x169mm, weight: 0.96kg.



### PRODUCT OVERVIEW

Product name	BEACON 93CRI 3K NARROW BEAM L1 TRAILING EDGE WHITE
Technology	LED
Housing	Aluminium
Mount	Track mounting
Environment	Internal
General application	Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	1512
Luminaire efficacy (lm/W)	72
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	93
Colour Consistency (SDCM)	3
Beam Angle (°)	12
Photobiological Risk Group	RG1
Total power consumption (W)	21
Product Voltage (V)	240
Electrical protection	Class II
Control gear type	Electronic ballast
Minimum dimming level (%)	97
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5025768595815

### PHOTOMETRY


## Beacon LED

*BEACON 93CRI 3K NARROW BEAM L1 TRAILING EDGE WHITE*  
**2059581**

0.5	0.11	E(0°) E(C0)	6.0° 6.0°	4208 2104
1.0	0.21	E(0°) E(C0)	6.0° 6.0°	1084 542
1.5	0.32	E(0°) E(C0)	6.0° 6.0°	470 235
2.0	0.42	E(0°) E(C0)	6.0° 6.0°	286 143
2.5	0.53	E(0°) E(C0)	6.0° 6.0°	176 88
3.0	0.63	E(0°) E(C0)	6.0° 6.0°	108 54

Distance [m]      Cone diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 12.0°)



## TECHNICAL DRAWINGS

