

### RefLED Retro MR11 RefLED RETRO MR11 184LM 3000K 36° SL 0028264



#### **Product features**

- LED MR11 range with the same look and feel of traditional halogen MR11 lamp
- Full glass design means no colours clashing between the lamp and fixture
- Available in 36 degree beam angle
- 15,000 hours average rated life
- Switching cycles: 50,000
- Colour rendering: CRI80
- Lamp voltage: 12V AC/DC
- Works with magnetic and compatible electronic transformers\*
- Warranty: 3 Years













#### PRODUCT OVERVIEW

Product name	RefLED RETRO MR11 184LM 3000K 36° SL
Technology	LED
Watt (Rated) (W)	2.5
Cap/Base	GU4
Fixture rating	Open
General application	Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4740807
Warranty	3 years
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Beam Angle (°)	36
Wattage (W)	2.5
Product Voltage (V)	12
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288282640

### **DATA TABLE**

Ger	eral	da	ta
acı	ıcıaı	ua	ιa

Product name	RefLED RETRO MR11 184LM 3000K 36° SL
Technology	LED
Watt (Rated) (W)	2.5
Cap/Base	GU4
Fixture rating	Open
General application	Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail



## RefLED Retro MR11 RefLED RETRO MR11 184LM 3000K 36° SL 0028264

Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740807
Warranty	3 years
•	•
Optical data	
Rated Luminous Flux Useful (Im)	184
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Rated Luminous Intensity (cd)	400
Beam Angle (°)	36
Lumen maintenance at end of nominal	70
life (%)	
Electrical data	
Wattage (W)	2.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	12
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Dimmable	No
kWh per 1000 hours burning time	3
Nominal Frequency (Hz)	DC/50/60/HF
Lifetime data	
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
• •	
Physical data	
Nominal Product Length (mm)	38
Nominal Product Diameter (mm)	35
Weight (kg)	0.017
Dookoging	
Packaging	
Single packaging type	Carton
Product EAN number	5410288282640
Packaging single length / height (cm)	5.0
Packaging single width (cm)	3.5
Packaging single depth (cm)	3.5
DUN14 (inner)	25410288282644
Units per inner package	10
Packaging inner length / height (cm)	6.0
Packaging inner width (cm)	8.0



# RefLED Retro MR11 RefLED RETRO MR11 184LM 3000K 36° SL 0028264

Packaging inner depth (cm)	19.0
DUN14 (outer)	15410288282647
Units per outer package	100
Packaging outer length / height (cm)	18.5
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	20.7

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Suitable for approved transf./dimmers
Safety message	Not Suitable for totally enclosed fixtures