

START eco Downlight 5in1 50-125

START eco Downlight 5in1 50-125 600LM
0053412



Product features

- START eco Downlight 5in1 is an integrated LED recessed / surface mounted downlight with built in non dimmable driver. Colour temperature (3000K, 4000K and 6500K) can be adjusted by a 3-way switch located on the back of the fixture. Adaptability to various cut-outs from 50mm to 125mm. 6W, 600lm, 100lm/W.



PRODUCT OVERVIEW

Product name	START eco Downlight 5in1 50-125 600LM
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4278099
Warranty	3 years
Fixture luminous flux (lm)	600
Luminaire efficacy (lm/W)	100
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	110
Glare control	< 22
Photobiological Risk Group	RG0
Total power consumption (W)	6
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK03
Product EAN number	5410288534121

PHOTOMETRY

START eco Downlight 5in1 50-125

START eco Downlight 5in1 50-125 600LM


0053412

0.5	1.51	1.51	E(0°)	832
			E(C90)	71
			E(C0)	71
1.0	3.01	3.02	E(0°)	208
			E(C90)	18
			E(C0)	18
1.5	4.52	4.53	E(0°)	92
			E(C90)	8
			E(C0)	8
2.0	6.02	6.04	E(0°)	52
			E(C90)	4
			E(C0)	4
2.5	7.53	7.55	E(0°)	33
			E(C90)	3
			E(C0)	3
3.0	9.03	9.07	E(0°)	23
			E(C90)	2
			E(C0)	2

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 113.0°)
 — C90 - C270 (Half beam angle: 112.8°)



0.5	1.51	1.51	E(0°)	832
			E(C90)	71
			E(C0)	71
1.0	3.01	3.02	E(0°)	208
			E(C90)	18
			E(C0)	18
1.5	4.52	4.53	E(0°)	92
			E(C90)	8
			E(C0)	8
2.0	6.02	6.04	E(0°)	52
			E(C90)	4
			E(C0)	4
2.5	7.53	7.55	E(0°)	33
			E(C90)	3
			E(C0)	3
3.0	9.03	9.07	E(0°)	23
			E(C90)	2
			E(C0)	2

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 113.0°)



0.5	1.51	1.51	E(0°)	832
			E(C90)	71
			E(C0)	71
1.0	3.01	3.02	E(0°)	208
			E(C90)	18
			E(C0)	18
1.5	4.52	4.53	E(0°)	92
			E(C90)	8
			E(C0)	8
2.0	6.02	6.04	E(0°)	52
			E(C90)	4
			E(C0)	4
2.5	7.53	7.55	E(0°)	33
			E(C90)	3
			E(C0)	3
3.0	9.03	9.07	E(0°)	23
			E(C90)	2
			E(C0)	2

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 113.0°)
 — C90 - C270 (Half beam angle: 112.8°)



TECHNICAL DRAWINGS

