Concord

Monitor LED
Monitor LED 3000K Silver
## 4055068

PRODUCT OVERVIEW

Product name	Monitor LED 3000K Silver
Technology	LED
Housing	Aluminium
Mount	Wall surface mounted
Environment	Exterior|Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail
ETIM Class	EC002892
Colour temperature (K)	3000
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral
Housing colour	Silver
IP rating	IP55
IK rating	IK10
Product EAN number	5026524550680

PHOTOMETRY

Distance [m]	Cone diameter [m]			Illuminance [lx]
0.5	1.56	E(0°)	57.3°	1292
		E(C0)		102
1.0	3.12	E(0°)	57.3°	323
		E(C0)		26
1.5	4.67	E(0°)	57.3°	144
		E(C0)		11
2.0	6.23	E(0°)	57.3°	81
		E(C0)		6
2.5	7.79	E(0°)	57.3°	52
		E(C0)		4
3.0	9.35	E(0°)	57.3°	36
		E(C0)		3

C0 - C180 (Half beam angle: 114.6°)

Monitor LED
Monitor LED 3000K Silver
4055068

Distance [m]	Cone diameter [m]			Illuminance [lx]
0.5	1.56	E(0°)	57.4°	684
		E(C0)		54
1.0	3.13	E(0°)	57.4°	171
		E(C0)		13
1.5	4.69	E(0°)	57.4°	76
		E(C0)		6
2.0	6.25	E(0°)	57.4°	43
		E(C0)		3
2.5	7.82	E(0°)	57.4°	27
		E(C0)		2
3.0	9.38	E(0°)	57.4°	19
		E(C0)		1

C0 - C180 (Half beam angle: 114.8°)

TECHNICAL DRAWINGS

350mm × 350mm