

Sylproof Tubular LED - Electronic

Sylproof Tubular LED 1X600 EB WW
0047586



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED



PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 1X600 EB WW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Fixture luminous flux (lm)	1287
Luminous flux (lm)	1287
Luminaire efficacy (lm/W)	99
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	13
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288475868


PHOTOMETRY

Sylproof Tubular LED - Electronic Sylproof Tubular LED 1X600 EB WW 0047586

0.5	1.14	E:07	1807
	1.78	E:C90	221
1.0	2.20	E:07	402
	3.56	E:C90	56
1.5	3.41	E:07	179
	5.35	E:C90	37
2.0	4.55	E:07	100
	7.13	E:C90	14
2.5	5.69	E:07	64
	8.91	E:C90	9
3.0	6.83	E:07	46
	10.63	E:C90	6

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 12.4°)
— C90 - C270 (Half beam angle: 97.4°)



TECHNICAL DRAWINGS

