

START Flex Low Output

START Flex IP65 827 2450lm
0068130



Product features

- 5 metre IP65 LED reel with pre-attached 3M adhesive type; equipped with 300 LEDs , 24V; 2700K; CRI80; SDCM 3





PRODUCT OVERVIEW

Product name	START Flex IP65 827 2450lm
Technology	LED
Housing	Other
Mount	Other
General application	Hospitality, Retail
ETIM Class	EC002706
E-number FI	4276596
Warranty	5 years
Fixture luminous flux (lm)	2450
Luminaire efficacy (lm/W)	102
Colour temperature (K)	2700
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Beam Angle (°)	N/A
Photobiological Risk Group	RG1
Total power consumption (W)	24
Electrical protection	Class III
Dimmable	Yes
Housing colour	Beige
IP rating	IP65
IK rating	IK00
Product EAN number	5410288681306

PHOTOMETRY

START Flex Low Output START Flex IP65 827 2450lm 0068130



Distance [m]	Core diameter [m]	Illuminance [lx]
0.5	1.52 1.35	888 99 73
1.0	2.04 2.70	187 14 18
1.5	4.57 4.05	74 6 9
2.0	6.09 5.41	42 4
2.5	7.61 6.76	27 2 3
3.0	9.13 8.11	19 2 3

Distance [m] Core diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 107.9°)
 — C90 - C270 (Half beam angle: 113.4°)

TECHNICAL DRAWINGS

