

RouteLED ROUTELED 3W STANDARD WHT 9192132



Product features

- Stand alone emergency luminaire downlight. Includes Standard lens, module (inverter) with 3.6v 4ah Ni-Cad batteries. 24hr recharge time. 1000mA discharge current. 700mA output current. Module size is 152x26.5x28.5mm - battery size is 38x270mm (Type 8). Module weight 150gm/battery weight 400gm.



PRODUCT OVERVIEW

Product name	ROUTELED 3W STANDARD WHT
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Internal
General application	Education, Hospitality, Office, Retail
E-number SE	7340460
Fixture luminous flux (lm)	194
Colour temperature (K)	6000
Beam Angle (°)	110
Total power consumption (W)	3
Housing colour	White
IP rating	IP20

DATA TABLE

General data

Product name	ROUTELED 3W STANDARD WHT
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Internal
General application	Education, Hospitality, Office, Retail
E-number SE	7340460

Optical data

Fixture luminous flux (lm)	194
Colour temperature (K)	6000
Correlated colour temperature range (K)	6000 - 6000
Adjustable chromaticity	N
Beam Angle (°)	110
Emergency duration (h)	3

RouteLED

ROUTELED 3W STANDARD WHT

9192132

Electrical data

Total power consumption (W)	3
Transformer required	Yes
Drive current (mA)	700

Physical data

Housing colour	White
IP rating	IP20
Cutout Dimensions (W x L in mm or Diameter in mm)	43
Weight (kg)	0.2
Recessed Depth (mm)	40

Packaging

Single packaging type	Carton
Packaging single length / height (cm)	5.0
Packaging single width (cm)	5.0
Packaging single depth (cm)	5.0
Units per outer package	1
Packaging outer length / height (cm)	5.0
Packaging outer width (cm)	5.0
Packaging outer depth (cm)	5.0

PHOTOMETRY

TECHNICAL DRAWINGS

