

Syl-Line electrical unit SYL-LINE GT3R 4K NR SI 0042151

Product features

- Syl-Line LED Gear Tray, 4000K Neutral White, Non Dimming, Narrow Beam, Silver




PRODUCT OVERVIEW

Product name	SYL-LINE GT3R 4K NR SI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting, Suspended
Environment	Interior
General application	Logistics & Industry, Retail
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	6476
Luminous flux (lm)	6476
Luminaire efficacy (lm/W)	132.16
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Photobiological Risk Group	RG0
Total power consumption (W)	49
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	Silver
IP rating	IP20
IK rating	IK02
Product EAN number	5410288421513

PHOTOMETRY

Syl-Line electrical unit SYL-LINE GT3R 4K NR SI 0042151



0.5	0.87 0.96	E(0°) E(C90) E(C0)	2149 702 712
1.0	1.15 1.11	E(0°) E(C90) E(C0)	839 178 193
1.5	1.72 1.67	E(0°) E(C90) E(C0)	288 77 79
2.0	2.29 2.23	E(0°) E(C90) E(C0)	134 43 44
2.5	2.86 2.78	E(0°) E(C90) E(C0)	69 21 21
3.0	3.44 3.34	E(0°) E(C90) E(C0)	49 16 16

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 45.0°)
— C90 - C270 (Half beam angle: 59.0°)

TECHNICAL DRAWINGS

