

## Beacon LED XXL

### BEACON XXL WB O/B DIM 4K L3 BLK

### 2093062



#### Product features

- 2093062 BEACON XXL WB O/B DIM 4K L3 BLK Integrated LED spotlight, black RAL 9005, compact and minimalist design, ideal for double height spaces, retail and display applications, die-cast aluminium body, passive cooling heatsink, beam angle: 67° wide beam, optics: Silicone lens for controlled beam, colour temperature: 4000K neutral white, total system power: 48W, total fixture output: 4884lm, luminaire efficacy: 102lm/W, LOR: 100%, colour rendering: Ra 93 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 1200mA, electronic driver, dimmable, on-board potentiometer for dimming control, power factor: 0.98 electrical protection: CLASS I, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, lockable p...




## PRODUCT OVERVIEW

Product name	BEACON XXL WB O/B DIM 4K L3 BLK
Technology	LED
Housing	Aluminium
Mount	Track mounting
Environment	Internal
General application	Retail
ETIM Class	EC001744
E-number FI	4278833
Warranty	5 years
Fixture luminous flux (lm)	4884
Luminaire efficacy (lm/W)	101.75
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	93
Colour Consistency (SDCM)	3
Beam Angle (°)	67
Photobiological Risk Group	RG1
Total power consumption (W)	48
Product Voltage (V)	240
Electrical protection	Class I
Control gear type	Electronic ballast
Minimum dimming level (%)	100
Housing colour	Black
IP rating	IP20
Product EAN number	5025768930623

## PHOTOMETRY

**Beacon LED XXL**  
*BEACON XXL WB O/B DIM 4K L3 BLK*  
**2093062**



## TECHNICAL DRAWINGS

