

Hydroproof LED G3 Emergency


HYDROPROOF LED G3 1200mm Single 4K E3

0048783



Product features

- Hydroproof, integrated LED chemical resistant weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface and wall mounting. GRP housing, PMMA diffuser, Non dimmable, 3 hour emergency, 4000K, CRI80, 4000 lm, 28 W, 142 lm/W, nominal average life (h):50000, energy class: A++ A+ A Class I, IK02, IP65.




PRODUCT OVERVIEW

Product name	HYDROPROOF LED G3 1200mm Single 4K E3
Technology	LED
Housing	Polyester
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	4000
Luminaire efficacy (lm/W)	142
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Beam Angle (°)	100
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	290
Total power consumption (W)	28
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	Grey
IP rating	IP65
IK rating	IK02
Product EAN number	5410288487830
Luminous flux (emergency) (lm)	290

PHOTOMETRY

Hydroproof LED G3 Emergency
HYDROPROOF LED G3 1200mm Single 4K E3
0048783



TECHNICAL DRAWINGS

