

Start Surface IP66 Ø350mm START SURFACE IP66 1500LM 840 IK10 WHT 0049001



Product features

- LED exterior surface mounted luminaire, 350mm diameter, 1500lm as max. lumen output, can be adjusted down to 730lm by internal switch, 14,5W power consumption max., 100lm/W efficacy, 4000K color temperature, CRI80, non-dimmable, IP66, IK10, 50,000 hours (L70), whitehousing, vandal resistant








PRODUCT OVERVIEW

Product name	START SURFACE IP66 1500LM 840 IK10 WHT
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Environment	Indoor, Outdoor
General application	Hospitality
ETIM Class	EC002892
E-number FI	4579479
Warranty	5 years
Fixture luminous flux (lm)	1500
Luminaire efficacy (lm/W)	103
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	14.5
Electrical protection	Class II
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP66
IK rating	IK10
Product EAN number	5410288490014

PHOTOMETRY

Start Surface IP66 Ø350mm *START SURFACE IP66 1500LM 840 IK10 WHT* 0049001



TECHNICAL DRAWINGS

