

## Sylproof Tubular LED - Electronic

*Sylproof Tubular LED 2X600 EB WW*  
0047589



### Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED




## PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 2X600 EB WW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Fixture luminous flux (lm)	2182
Luminous flux (lm)	2182
Luminaire efficacy (lm/W)	103.9
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	21
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288475899

## PHOTOMETRY

## Sylproof Tubular LED - Electronic Sylproof Tubular LED 2X600 EB WW 0047589



0.5	1.12 2.16	E(0°) E(90°) E(180°)	250 399 84
1.0	2.24 4.33	E(0°) E(90°) E(180°)	633 999 21
1.5	3.36 6.49	E(0°) E(90°) E(180°)	251 41 10
2.0	4.48 8.66	E(0°) E(90°) E(180°)	168 23 6
2.5	5.60 10.82	E(0°) E(90°) E(180°)	101 15 4
3.0	6.72 12.99	E(0°) E(90°) E(180°)	70 10 3

Distance [m]      Cone diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 180°)

— C90 - C270 (Half beam angle: 90°)

### TECHNICAL DRAWINGS

