

Sylproof Tubular LED - Microwave sensor DALI

Sylproof Tubular LED 2X1500 DALI MW WW
0047633



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED




PRODUCT OVERVIEW

| | |
|-----------------------------|----------------------------------------|
| Product name | Sylproof Tubular LED 2X1500 DALI MW WW |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Acrylic PMMA |
| Mount | Ceiling surface mounting |
| Environment | Interior |
| General application | Logistics & Industry |
| ETIM Class | EC000109 |
| Warranty | 5 years |
| Fixture luminous flux (lm) | 5597 |
| Luminous flux (lm) | 5597 |
| Luminaire efficacy (lm/W) | 115.4 |
| LOR (%) | 100 |
| Colour temperature (K) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 80 |
| Colour Consistency (SDCM) | 3 |
| Photobiological Risk Group | RG0 |
| Total power consumption (W) | 48.5 |
| Electrical protection | Class I |
| Control gear type | Electronic ballast |
| Dimmable | Yes |
| Minimum dimming level (%) | 90 |
| Housing colour | Transparent |
| IP rating | IP66 |
| IK rating | IK06 |
| Product EAN number | 5410288476339 |

PHOTOMETRY

Sylproof Tubular LED - Microwave sensor DALI *Sylproof Tubular LED 2X1500 DALI MW WW* 0047633



| | | | |
|-----|---------------|----------------------------|--------------------|
| 0.5 | 1.16 2.19 | E(0°) E(90°) E(180°) | 6422 396 229 |
| 1.0 | 2.32 4.39 | E(0°) E(90°) E(180°) | 1605 224 147 |
| 1.5 | 3.48 6.58 | E(0°) E(90°) E(180°) | 714 102 65 |
| 2.0 | 4.63 8.78 | E(0°) E(90°) E(180°) | 401 55 34 |
| 2.5 | 5.79 10.97 | E(0°) E(90°) E(180°) | 257 35 21 |
| 3.0 | 6.95 13.17 | E(0°) E(90°) E(180°) | 178 25 16 |

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 181.0°)
 — C90 - C270 (Half beam angle: 98.4°)

TECHNICAL DRAWINGS

