

Lynx L

LYNX-L 36W/865 10-WAY

0025663



Product features

- - Compact size alternative for tubular fluorescent lamps, - Suitable for operation on electronic and electromagnetic control gears, - Excellent colour rendering, - Dimmable with suitable ballast

Lynx L

LYNX-L 36W/865 10-WAY
0025663



PRODUCT OVERVIEW

Product name	LYNX-L 36W/865 10-WAY
Technology	Compact Fluorescent
Watt (Rated) (W)	36.00
Lamp shape	Other
Type	Lynx L
Cap/Base	2G11
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000087
Luminous flux (lm)	2600
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	82
Wattage (W)	36.00
Product Voltage (V)	106
Dimmable	Yes
Average life (Nominal) (h)	16000
Product EAN number	5410288256634

DATA TABLE

General data

Product name	LYNX-L 36W/865 10-WAY
Technology	Compact Fluorescent
Watt (Rated) (W)	36.00
Lamp shape	Other
Type	Lynx L
Cap/Base	2G11
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000087

Optical data

Luminous flux (lm)	2600
Luminous flux (Rated) (lm)	2600

Lynx L

LYNX-L 36W/865 10-WAY
0025663

Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	6500
Light colour	Daylight
Colour Code	865
CRI (Ra)	82
Adjustable chromaticity	N
Rated lumen maint. factor (%) at 4000 h 50Hz	78
Rated lumen maint. factor (%) at 8000 h 50Hz	76
Rated lumen maint. factor (%) at 16000 h 50Hz	70

Electrical data

Wattage (W)	36.00
Starting time (max) (s)	<10
Warm-up time to 60% of full light (max) (s)	60
Current (A)	0.436
Mains voltage (V)	220-240V~
Product Voltage (V)	106
Ignition voltage (V)	198
Control gear required	Yes
Transformer required	No
Dimmable	Yes
Lamp Energy Label (class)	G
kWh per 1000 hours burning time	40

Lifetime data

Average life (Nominal) (h)	16000
Average life (Rated) (h)	16000
Rated survival factor (%) at 2000 h 50Hz	98
Rated survival factor (%) at 4000 h 50Hz	90
Rated survival factor (%) at 6000 h 50Hz	85
Rated survival factor (%) at 8000 h 50Hz	80
Rated survival factor (%) at 12000 h 50Hz	78
Rated survival factor (%) at 16000 h 50Hz	50

Physical data

Weight (kg)	0.12
-------------	------

Packaging

Single packaging type	Carton
Product EAN number	5410288256634
Packaging single length / height (cm)	43.2
Packaging single width (cm)	4.5
Packaging single depth (cm)	2.5
DUN14 (inner)	25410288256638

Lynx L

LYNX-L 36W/865 10-WAY
0025663

Units per inner package	10
Packaging inner length / height (cm)	44.2
Packaging inner width (cm)	10.0
Packaging inner depth (cm)	14.0
DUN14 (outer)	15410288256631
Units per outer package	50
Packaging outer length / height (cm)	53.0
Packaging outer width (cm)	46.5
Packaging outer depth (cm)	16.5

Safety data

Lamp mercury content (mg)	3.00
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	Yes
Suitable for accent lighting	N/A