

# Syl-Line electrical unit SYL-LINE GT3R 4K DASY WH 0042114

#### **Product features**

Syl-Line LED Gear Tray, 4000K Neutral White, Non Dimming, Double Asymmetric Beam, White


















#### PRODUCT OVERVIEW


Technology Cap/Base N/A Housing Aluminium Mount Ceiling surface mounting, Suspended Environment Interior General application ETIM Class EC000109 Warranty 5 years Fixture luminous flux (Im) 6535 Luminous flux (Im) 6535 Luminaire efficacy (Im/W) 133.37 LOR (%) 100 Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) Photobiological Risk Group RG0	Product name	SYL-LINE GT3R 4K DASY WH
Housing Aluminium  Mount Ceiling surface mounting, Suspended Environment Interior General application Logistics & Industry, Retail ETIM Class EC000109  Warranty 5 years Fixture luminous flux (Im) 6535 Luminous flux (Im) 6535  Luminaire efficacy (Im/W) 133.37  LOR (%) 100  Colour temperature (K) 4000  Light colour Neutral White CRI (Ra) 80	Technology	LED
Mount Ceiling surface mounting, Suspended Environment Interior General application Logistics & Industry, Retail ETIM Class EC000109 Warranty 5 years Fixture luminous flux (Im) 6535 Luminous flux (Im) 6535 Luminaire efficacy (Im/W) 133.37 LOR (%) 100 Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80	Cap/Base	N/A
Environment Interior  General application Logistics & Industry, Retail  ETIM Class EC000109  Warranty 5 years  Fixture luminous flux (Im) 6535  Luminous flux (Im) 6535  Luminaire efficacy (Im/W) 133.37  LOR (%) 100  Colour temperature (K) 4000  Light colour Neutral White  CRI (Ra) 80	Housing	Aluminium
General application  ETIM Class  EC000109  Warranty  5 years  Fixture luminous flux (Im)  6535  Luminous flux (Im)  6535  Luminaire efficacy (Im/W)  133.37  LOR (%)  Colour temperature (K)  Light colour  CRI (Ra)  Logistics & Industry, Retail  EC000109  5 years  6535  Luminous flux (Im)  6535  Luminaire efficacy (Im/W)  100  Colour temperature (K)  4000  Neutral White	Mount	Ceiling surface mounting, Suspended
ETIM Class         EC000109           Warranty         5 years           Fixture luminous flux (Im)         6535           Luminaire efficacy (Im/W)         133.37           LOR (%)         100           Colour temperature (K)         4000           Light colour         Neutral White           CRI (Ra)         80	Environment	Interior
Warranty         5 years           Fixture luminous flux (Im)         6535           Luminous flux (Im)         6535           Luminaire efficacy (Im/W)         133.37           LOR (%)         100           Colour temperature (K)         4000           Light colour         Neutral White           CRI (Ra)         80	General application	Logistics & Industry, Retail
Fixture luminous flux (Im)         6535           Luminous flux (Im)         6535           Luminaire efficacy (Im/W)         133.37           LOR (%)         100           Colour temperature (K)         4000           Light colour         Neutral White           CRI (Ra)         80	ETIM Class	EC000109
Luminous flux (Im)6535Luminaire efficacy (Im/W)133.37LOR (%)100Colour temperature (K)4000Light colourNeutral WhiteCRI (Ra)80	Warranty	5 years
Luminaire efficacy (Im/W) 133.37  LOR (%) 100  Colour temperature (K) 4000  Light colour Neutral White  CRI (Ra) 80	Fixture luminous flux (lm)	6535
LOR (%) 100 Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80	Luminous flux (lm)	6535
Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80	Luminaire efficacy (lm/W)	133.37
Light colour Neutral White CRI (Ra) 80	LOR (%)	100
<b>CRI (Ra)</b> 80	Colour temperature (K)	4000
	Light colour	Neutral White
Photobiological Risk Group RG0	CRI (Ra)	80
	Photobiological Risk Group	RG0
Total power consumption (W) 49	Total power consumption (W)	49
Electrical protection Class I	Electrical protection	Class I
Control gear type Electronic ballast	Control gear type	Electronic ballast
<b>Dimmable</b> No	Dimmable	No
Housing colour White	Housing colour	White
IP rating IP20	IP rating	IP20
IK rating IK02	IK rating	IK02
Product EAN number 5410288421148	Product EAN number	5410288421148

### **PHOTOMETRY**



## Syl-Line electrical unit SYL-LINE GT3R 4K DASY WH 0042114





### **TECHNICAL DRAWINGS**

