


Myriad Adjustable Square - White with Silver bezel

MYRIAD ADJ SQUARE WHITE 3000K PHDIM SILVER BEZ
2056226



Product features

- The Myriad Adjustable Square recessed spotlight is a high efficient accent downlight, fixture color RAL 9016 - Traffic white / Bezel, correlated colour temperature of 3000K, color rendering index Ra103, fixture lumen 702lm, total power consumption 10W, luminaire efficacy 70 lm/W, nominal light beam angle 24°, mains voltage 230-240V~ AC, control technology type: leading edge/trailing edge phase dim, product length 76mm, width 76mm, height 115mm, cut-out dimension 72x72mm, IP rating IP20, 5 years warranty.



PRODUCT OVERVIEW

Product name	MYRIAD ADJ SQUARE WHITE 3000K PHDIM SILVER BEZ
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Hospitality, Office, Retail, Residential & Consumer
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	702
Luminaire efficacy (lm/W)	70
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	24
Photobiological Risk Group	RG1
Total power consumption (W)	10
Electrical protection	Class II
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5025768562268

DATA TABLE

General data

Product name	MYRIAD ADJ SQUARE WHITE 3000K PHDIM SILVER BEZ
Technology	LED

Myriad Adjustable Square - White with Silver bezel

MYRIAD ADJ SQUARE WHITE 3000K PHDIM SILVER BEZ
2056226

Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Hospitality, Office, Retail, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Warranty	5 years

Optical data

Fixture luminous flux (lm)	702
Luminaire efficacy (lm/W)	70
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Adjustable chromaticity	N
Beam Angle (°)	24
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	10
Mains voltage (V)	230-240V~
Electrical protection	Class II
Transformer required	Yes
Drive current (mA)	250
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Lifespan L70 B50	50000
------------------	-------

Physical data

Housing colour	White
IP rating	IP20
IK rating	IK02
Nominal Product Width (mm)	76
Nominal Product Height (mm)	115
Weight (kg)	0.38
Recessed Depth (mm)	115

Packaging


Single packaging type	Carton
Product EAN number	5025768562268
Packaging single length / height (cm)	17.5
Packaging single width (cm)	15.0
Packaging single depth (cm)	17.5

Myriad Adjustable Square - White with Silver bezel

MYRIAD ADJ SQUARE WHITE 3000K PHDIM SILVER BEZ
2056226

DUN14 (outer)	05025768562268
Units per outer package	1
Packaging outer length / height (cm)	17.5
Packaging outer width (cm)	15.0
Packaging outer depth (cm)	17.5

PHOTOMETRY



Distance [m]	Cone diameter [m]	E(0°) E(C0)	Illuminance [lx]
0.5	0.23	1203 602	1203 602
1.0	0.47	312 156	312 156
1.5	0.70	139 64	139 64
2.0	0.94	78 36	78 36
2.5	1.17	50 23	50 23
3.0	1.41	34 16	34 16

Distance [m] Cone diameter [m] Illuminance [lx]
C0 - C180 (Half beam angle: 26.4°)

TECHNICAL DRAWINGS

