

Sylproof Tubular LED - Microwave sensor DALI

Sylproof Tubular LED 2X600 DALI MW WW
0047631



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED



PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 2X600 DALI MW WW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	2182
Luminous flux (lm)	2182
Luminaire efficacy (lm/W)	103.9
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	21
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	90
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476315

PHOTOMETRY


Sylproof Tubular LED - Microwave sensor DALI Sylproof Tubular LED 2X600 DALI MW WW 0047631

Distance [m]	Core diameter [m]	E _{0%}	E _{5%}	E _{10%}	Beam diameter [m]
0.5	1.13 2.16	2300	48.9°	399	34
1.0	2.26 4.33	833	48.9°	92	23
1.5	3.39 6.49	231	48.9°	41	15
2.0	4.52 8.66	188	48.9°	23	8
2.5	5.65 10.82	101	48.9°	15	4
3.0	6.78 12.99	70	48.9°	10	3

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 150 °)

— C90 - C270 (Half beam angle: 97 °)



TECHNICAL DRAWINGS

