

DALI CV DRIVER DALI 100W 24V 9014927



Product features

- Constant voltage driver, 100W, 24V Tridonic branded LED driver with One4all and ready2mains dimming options (with PWM dimmers), 50,000 h nominal life-time, small design (295 x 43 x 30 mm), push terminals for simple wiring, suitable for cove lighting, facade accent lighting, ceiling integration. Tridonic code: 28001253.



PRODUCT OVERVIEW

| | |
|---------------------|-------------------------|
| Product name | CV DRIVER DALI 100W 24V |
| Technology | Accessory |
| General application | Retail |
| ETIM Class | EC002710 |
| E-number FI | 4045138 |
| Warranty | 5 years |
| Product Voltage (V) | 24 |
| Dimmable | Yes |
| Product EAN number | 9006210563992 |
| Max load (A) | 4 |

DATA TABLE

General data

| | |
|----------------------------------|-------------------------|
| Product name | CV DRIVER DALI 100W 24V |
| Technology | Accessory |
| General application | Retail |
| Operating temperature range (°C) | -25°C - 50°C |
| ETIM Class | EC002710 |
| E-number FI | 4045138 |
| Warranty | 5 years |

Electrical data

| | |
|-----------------------------------|-----------|
| Mains voltage (V) | 220-240V~ |
| Product Voltage (V) | 24 |
| Dimmable | Yes |
| Max. Luminaires per 10A C Breaker | 12 |
| Max. Luminaires per 13A C Breaker | 16 |
| Max. Luminaires per 16A C Breaker | 18 |
| Max. Luminaires per 20A C Breaker | 26 |
| Max. Luminaires per 10A B Breaker | 6 |
| Max. Luminaires per 13A B Breaker | 8 |
| Max. Luminaires per 16A B Breaker | 9 |

DALI CV DRIVER DALI 100W 24V 9014927

| | |
|-----------------------------------|----|
| Max. Luminaires per 20A B Breaker | 13 |
|-----------------------------------|----|

Physical data

| | |
|-----------------------------|-------|
| Nominal Product Length (mm) | 295 |
| Nominal Product Width (mm) | 43 |
| Nominal Product Height (mm) | 29.8 |
| Weight (kg) | 0.254 |

Packaging

| | |
|---------------------------------------|-------------------|
| Single packaging type | Without Packaging |
| Product EAN number | 9006210563992 |
| Packaging single length / height (cm) | 29.5 |
| Packaging single width (cm) | 4.3 |
| Packaging single depth (cm) | 2.98 |
| Units per outer package | 10 |
| Packaging outer length / height (cm) | 37.3 |
| Packaging outer width (cm) | 18.0 |
| Packaging outer depth (cm) | 10.4 |

Safety data

| | |
|----------------------------------|--------|
| Optimal operating condition (°C) | -25-50 |
|----------------------------------|--------|

TECHNICAL DRAWINGS

