

Sylproof Tubular LED - Microwave sensor

Sylproof Tubular LED 1X600 EB MW WW
0047616



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED



PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 1X600 EB MW WW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	1287
Luminous flux (lm)	1287
Luminaire efficacy (lm/W)	99
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	13
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476162

PHOTOMETRY


Sylproof Tubular LED - Microwave sensor

Sylproof Tubular LED 1X600 EB MW WW
0047616

0.5	1.14	E07	1807
	1.78	E(C90)	221
1.0	2.20	E07	402
	3.56	E(C90)	56
1.5	3.41	E07	179
	5.35	E(C90)	37
2.0	4.55	E07	100
	7.13	E(C90)	14
2.5	5.69	E07	64
	8.91	E(C90)	9
3.0	6.83	E07	46
	10.69	E(C90)	6

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 12.4°)
— C90 - C270 (Half beam angle: 97.4°)



TECHNICAL DRAWINGS

