

Start Spot Scoop

START SPOT SCOOP 1050LM 930 MB WHITE

0060580



Product features

- Recessed Adjustable Accent Downlight, integrated LED, die cast aluminium body, Ø115mm cut-out, CCT 3000K, SDCM<3, CRI90, 1050lm, total power consumption 12W, resulting in 88lm/W.




PRODUCT OVERVIEW

Product name	START SPOT SCOOP 1050LM 930 MB WHITE
Technology	LED
Housing	Aluminium
Environment	Indoor
General application	Retail
ETIM Class	EC001744
E-number FI	4276977
Warranty	5 years
Fixture luminous flux (lm)	1050
Luminaire efficacy (lm/W)	88
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	32
Photobiological Risk Group	RG1
Total power consumption (W)	12
Electrical protection	Class II
Dimmable	No
LED Flickering Rate	Medium (21% - 40%)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK03
Product EAN number	5410288605807

PHOTOMETRY

Start Spot Scoop *START SPOT SCOOP 1050LM 930 MB WHITE* 0060580



Distance [m]	Cone diameter [m]	E0%	E1%	E5%	E10%	E15%	E20%	E30%	E40%	E50%	E60%	E70%	E80%	E90%	Beam diameter [m]	Illuminance [lx]
0.5	0.30	50%	50%	16%	16%	8%	8%	4%	4%	2%	2%	1%	1%	0%	0.30	894
1.0	0.61	50%	50%	16%	16%	8%	8%	4%	4%	2%	2%	1%	1%	0%	0.61	214
1.5	0.91	50%	50%	16%	16%	8%	8%	4%	4%	2%	2%	1%	1%	0%	0.91	95
2.0	1.22	50%	50%	16%	16%	8%	8%	4%	4%	2%	2%	1%	1%	0%	1.22	58
2.5	1.52	50%	50%	16%	16%	8%	8%	4%	4%	2%	2%	1%	1%	0%	1.52	34
3.0	1.82	50%	50%	16%	16%	8%	8%	4%	4%	2%	2%	1%	1%	0%	1.82	23

TECHNICAL DRAWINGS

