

Granit 0-10V

Granit IP65 0-10V 13000lm 840 MB

0039592

Product features

- Integrated LED highbay; Black aluminium housing; 13000Lm; 90 W; 144 Lm/W; 4000K; Drive current: 780mA; CRI 80; 55° beam angle; 0-10V dimmable; IP65; IK08; Lifespan L80:B50 90,000 hrs; (D x H) 308 x 166 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.



PRODUCT OVERVIEW









Product name	Granit IP65 0-10V 13000lm 840 MB
Technology	LED
Housing	Aluminium
Mount	Suspended
General application	Logistics & Industry
ETIM Class	EC001716
E-number FI	4357002
Warranty	5 years
Fixture luminous flux (lm)	13000
Luminaire efficacy (lm/W)	144
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	55
Glare control	< 22
Photobiological Risk Group	RG1
Total power consumption (W)	90
Electrical protection	Class I
Control gear type	Other
Dimmable	Yes
LED Flickering Rate	Low (6% - 20%)
Housing colour	Black
IP rating	IP65
IK rating	IK08
Product EAN number	5410288395920

Granit 0-10V

Granit IP65 0-10V 13000lm 840 MB

0039592

PHOTOMETRY



TECHNICAL DRAWINGS

Granit 0-10V

Granit IP65 0-10V 13000lm 840 MB

0039592

