

ToLEDo Performer T-Series

ToLEDo Performer T60 3400LM 840 E27 SL
0028370



Product features



- Direct retrofit replacement for high-pressure mercury vapor lamps (HPMV) 50,000 hours average rated lifetime Up to 78% energy saving compared to the standard high-pressure mercury vapor lamps Mercury-free solution Lower maintenance cost High lumen efficacy Dual operating mode - compatible with HPMV magnetic ballast and also, suitable for AC direct mains 120-240V operation High surge voltage protection: 4kV Suitable for both open and enclosed luminaires Wide light distribution High switching cycles - 200,000X High colour rendering - CRI80 Minimum and maximum operating temperature: -30°C to 50°C



PRODUCT OVERVIEW

| | |
|---------------------------------|--|
| Product name | ToLEDo Performer T60 3400LM 840 E27 SL |
| Technology | LED |
| Watt (Rated) (W) | 27 |
| Type | LED exchangeable |
| Cap/Base | E27 |
| Fixture rating | Open |
| General application | Logistics & Industry |
| ETIM Class | EC001959 |
| E-number FI | 4740739 |
| Warranty | 5 years |
| Luminous flux (lm) | 3400 |
| Colour temperature (K) | 4000 |
| Light colour | Cool White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Photobiological Risk Group | RG1 |
| Wattage (W) | 27 |
| Product Voltage (V) | 230 |
| Dimmable | No |
| Average life (Nominal) (h) | 50000 |
| Product EAN number | 5410288283708 |

PHOTOMETRY



ToLEDo Performer T-Series

ToLEDo Performer T60 3400LM 840 E27 SL

0028370

TECHNICAL DRAWINGS

