





## START eco Downlight 5in1 55-175 *START eco Downlight 5in1 55-175 1850LM* 0053414

Distance [m]	Cone diameter [m]	E0°	E10°	E30°	E45°	E60°	E75°	E90°
0.5	1.50 1.52	2302	201	198	196	194	192	190
1.0	3.00 3.04	580	50	49	48	47	46	45
1.5	4.50 4.57	392	32	31	30	29	28	27
2.0	6.00 6.08	285	23	22	21	20	19	18
2.5	7.50 7.61	217	17	16	15	14	13	12
3.0	9.00 9.13	167	13	12	11	10	9	8

Distance [m] Cone diameter [m] Illuminance [lx]  
 C0 - C180 (Half beam angle: 113.4°)  
 C90 - C270 (Half beam angle: 112.4°)


Distance [m]	Cone diameter [m]	E0°	E10°	E30°	E45°	E60°	E75°	E90°
0.5	1.49 1.52	2660	221	218	215	212	209	206
1.0	2.99 3.04	660	55	54	53	52	51	50
1.5	4.48 4.57	440	36	35	34	33	32	31
2.0	5.98 6.08	330	27	26	25	24	23	22
2.5	7.47 7.61	255	20	19	18	17	16	15
3.0	8.96 9.13	195	15	14	13	12	11	10

Distance [m] Cone diameter [m] Illuminance [lx]  
 C0 - C180 (Half beam angle: 113.4°)  
 C90 - C270 (Half beam angle: 112.4°)



Distance [m]	Cone diameter [m]	E0°	E10°	E30°	E45°	E60°	E75°	E90°
0.5	1.49 1.52	2302	201	198	196	194	192	190
1.0	2.99 3.04	580	50	49	48	47	46	45
1.5	4.48 4.57	392	32	31	30	29	28	27
2.0	5.98 6.08	285	23	22	21	20	19	18
2.5	7.47 7.61	217	17	16	15	14	13	12
3.0	8.96 9.13	167	13	12	11	10	9	8

Distance [m] Cone diameter [m] Illuminance [lx]  
 C0 - C180 (Half beam angle: 113.4°)  
 C90 - C270 (Half beam angle: 112.4°)



### TECHNICAL DRAWINGS

