

START Panel Flat 600x600


START Panel Flat 600x600 4000Lm 830

0047212



Product features

- Edge lit LED flat panel. Low Flicker, 40 W, Warm White, 3000 K, 4000 lumens, 100 lm/W, Average lifespan: 120.000Hrs, PMMA opal diffuser, aluminium frame, steel body, electronic non dimmable driver. (HxWxD) 9.5 x 595 x 595 mm




PRODUCT OVERVIEW

Product name	START Panel Flat 600x600 4000Lm 830
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting, Ceiling surface mounting, Suspended
Environment	Interior
General application	Education, Office
ETIM Class	EC002892
E-number FI	4276933
Warranty	5 years
Fixture luminous flux (lm)	4,000
Luminaire efficacy (lm/W)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	40
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP40/20
IK rating	IK03
Product EAN number	5410288472126

PHOTOMETRY

START Panel Flat 600x600

START Panel Flat 600x600 4000Lm 830
0047212



TECHNICAL DRAWINGS

