

Start Waterproof T8 START WATERPROOF T8 PC 1x36 EB 0045818



Product features

Start Waterproof T8 weatherproof luminaire, Polycarbonate housing, Polycarbonate Diffuser, 1 x 36W, Non Dimmable Electronic Ballast, IP66, IK08, Lamp not included, To be used with LFL tubes













PRODUCT OVERVIEW

Product name	START WATERPROOF T8 PC 1x36 EB
Technology	Fluorescent
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC002892
Warranty	2 years
Light colour	N/A
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral
Housing colour	Grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288458182

DATA TABLE

General data	
Product name	START WATERPROOF T8 PC 1x36 EB
Technology	Fluorescent
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
Operating temperature range (°C)	-20°C - 25°C
ETIM Class	EC002892
Warranty	2 years
Optical data	
Light colour	N/A
Adjustable chromaticity	N
Electrical data	
Mains voltage (V)	220-240V~



Start Waterproof T8 START WATERPROOF T8 PC 1x36 EB 0045818

Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral
Transformer required	Yes
Nominal Frequency (Hz)	50/60Hz
Physical data	
Housing colour	Grey
ID :	IDO


IP rating	IP66
IK rating	IK08
Diffuser finish	Prismatic
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1277
Nominal Product Width (mm)	90
Nominal Product Height (mm)	100
Weight (kg)	1.553

Packaging

Single packaging type	Carton
Product EAN number	5410288458182
Packaging single length / height (cm)	127.7
Packaging single width (cm)	9.0
Packaging single depth (cm)	9.3
DUN14 (outer)	05410288458182
Units per outer package	1
Packaging outer length / height (cm)	127.7
Packaging outer width (cm)	9.0
Packaging outer depth (cm)	9.3

-20-25

PHOTOMETRY



Optimal operating condition (°C)



Start Waterproof T8
START WATERPROOF T8 PC 1x36 EB
0045818

TECHNICAL DRAWINGS

