

CMI-T Mini CMI-TMINI 20W/WDL GU6.5 0020311



PRODUCT OVERVIEW

Product name	CMI-TMINI 20W/WDL GU6.5
Technology	HID
Watt (Rated) (W)	20
Type	CMI-T mini
Cap/Base	GU6.5
Lamp finish	Clear
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail
E-number SE	8359021
Luminous flux (lm)	1900
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	85
Wattage (W)	20
Product Voltage (V)	90
Average life (Nominal) (h)	18000
Product EAN number	5410288203119

DATA TABLE

General data

Product name	CMI-TMINI 20W/WDL GU6.5
Technology	HID
Watt (Rated) (W)	20
Type	CMI-T mini
Cap/Base	GU6.5
Lamp finish	Clear
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail
E-number SE	8359021

Optical data

CMI-T Mini

CMI-TMINI 20W/WDL GU6.5

0020311

Luminous flux (lm)	1900
Luminous flux (Rated) (lm)	1900
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	3000
Light colour	Warm White
Colour Code	830
CRI (Ra)	85
Adjustable chromaticity	N
Rated lumen maint. factor (%) at 4000 h 50Hz	73
Rated lumen maint. factor (%) at 6000 h 50Hz	71
Rated lumen maint. factor (%) at 8000 h 50Hz	69
Rated lumen maint. factor (%) at 12000 h 50Hz	67
Rated lumen maint. factor (%) at 16000 h 50Hz	65

Electrical data

Wattage (W)	20
Current (A)	0.22
Product Voltage (V)	90
Control gear required	Yes
Transformer required	Yes
kWh per 1000 hours burning time	22

Lifetime data

Average life (Nominal) (h)	18000
Average life (Rated) (h)	18000
Life T90	10000
Rated survival factor (%) at 2000 h 50Hz	100
Rated survival factor (%) at 4000 h 50Hz	73
Rated survival factor (%) at 6000 h 50Hz	71
Rated survival factor (%) at 8000 h 50Hz	69
Rated survival factor (%) at 12000 h 50Hz	67
Rated survival factor (%) at 16000 h 50Hz	78
Rated survival factor (%) at 20000 h 50Hz	100

Physical data

Max. Lamp Diameter (mm) - D	13
Weight (kg)	0.006

Packaging

Single packaging type	Carton
Product EAN number	5410288203119
Packaging single length / height (cm)	2.5

CMI-T Mini

CMI-TMINI 20W/WDL GU6.5

0020311

Packaging single width (cm)	2.5
Packaging single depth (cm)	7.0
DUN14 (inner)	15410288203116
Units per inner package	12
Packaging inner length / height (cm)	8.33
Packaging inner width (cm)	7.9
Packaging inner depth (cm)	11.1
DUN14 (outer)	35410288203110
Units per outer package	96
Packaging outer length / height (cm)	34.6
Packaging outer width (cm)	8.8
Packaging outer depth (cm)	23.1

Safety data

Lamp mercury content (mg)	2.60
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Suitable for household illumination	No